


E 721

Raccordi di Riduzione Maschio — Femmina con Guarnizione
Male — Female Reducing Adapters with Captive Seal
Reduzierstutzen mit Dichtung

ISO 1179-1 / ISO 1179-2

Filettatura: BSP cilindrica (DIN ISO 228) - Thread: BSP cyl. (DIN ISO 228) - Gewinde: BSP zyl. (DIN ISO 228)



Pressione Pressure Druck	CODICE Part n° Bestell. nr.	DESCRIZIONE Description Bestellzeichen	Ø F1	Ø F2	S1	Ø D1	L1	L2	L3
PN 400	E 721 0 110 104	E 721 - 3/8" - 1/8"	G 3/8"	G 1/8"	22	22	22,5	12	9
PN 400	E 721 0 113 104	E 721 - 1/2" - 1/8"	G 1/2"	G 1/8"	27	27	24	14	9
PN 400	E 721 0 113 106	E 721 - 1/2" - 1/4"	G 1/2"	G 1/4"	27	27	24	14	13
PN 315	E 721 0 119 106	E 721 - 3/4" - 1/4"	G 3/4"	G 1/4"	32	32	26	16	13
PN 315	E 721 0 119 110	E 721 - 3/4" - 3/8"	G 3/4"	G 3/8"	32	32	26	16	14
PN 315	E 721 0 125 106	E 721 - 1" - 1/4"	G 1"	G 1/4"	41	40	29	18	14
PN 315	E 721 0 125 110	E 721 - 1" - 3/8"	G 1"	G 3/8"	41	40	29	18	14
PN 315	E 721 0 125 113	E 721 - 1" - 1/2"	G 1"	G 1/2"	41	40	29	18	16
PN 315	E 721 0 132 113	E 721 - 1"1/4 - 1/2"	G 1"1/4	G 1/2"	50	50	32	20	16
PN 315	E 721 0 132 119	E 721 - 1"1/4 - 3/4"	G 1"1/4	G 3/4"	50	50	32	20	18
PN 250	E 721 0 138 113	E 721 - 1"1/2 - 1/2"	G 1"1/2	G 1/2"	55	55	36	22	16
PN 250	E 721 0 138 119	E 721 - 1"1/2 - 3/4"	G 1"1/2	G 3/4"	55	55	36	22	18
PN 250	E 721 0 138 125	E 721 - 1"1/2 - 1"	G 1"1/2	G 1"	55	55	36	22	20

Temperature di utilizzo senza riduzione di pressione con guarnizioni in NBR: da -35° a +100°C.

Permissible working temperatures without reductions in pressure for captive seals in NBR: -35° to +120°C.

Zulässige Betriebstemperatur ohne Druckabschläge für Dichtungen aus NBR: -35° bis +100°C.