


Raccordi Femmina Sede JIC 74°
JIC Females 74° Cone
JIC 74° Dichtkegel

ISO 12151-5 (ISO 8434-2)

DKJ



	CODICE Part n° Bestell. nr.	Filetto Thread Gewinde	Ø F ø F ø F	DN Tubo ND Hose DN Schlauch	CH	L	Ø C	H	M
a	S 30 43 0 604 005	7/16" -20 UNF		3/16" 05	14	45,5	3	23,5	14
a	S 30 43 0 604 006	7/16" -20 UNF		1/4" 06	14	51,5	4	23,5	14
a	S 30 43 0 606 006	1/2" -20 UNF		1/4" 06	17	52,5	4	24,5	15
a	S 30 43 0 606 008	1/2" -20 UNF		5/16" 08	17	52,5	5,5	24,5	15
a	S 30 43 0 608 006	9/16" -18 UNF		1/4" 06	19	54,5	4	26,5	16,5
a	S 30 43 0 608 008	9/16" -18 UNF		5/16" 08	19	55	5,5	27	17
a	S 30 43 0 608 010	9/16" -18 UNF		3/8" 10	19	56	7	26,5	16,5
a	S 30 43 0 610 010	3/4" -16 UNF		3/8" 10	24	60	7	30,5	19
a	S 30 43 0 610 013	3/4" -16 UNF		1/2" 13	24	59,5	9,5	30	18,5
a	S 30 43 0 613 010	7/8" -14 UNF		3/8" 10	27	63	7	33,5	20
a	S 30 43 0 613 013	7/8" -14 UNF		1/2" 13	27	64,5	9,5	35	21
a	S 30 43 0 613 016	7/8" -14 UNF		5/8" 16	27	67,5	12,5	33,5	19,5
a	S 30 43 0 619 013	1"1/16 - 12 UN		1/2" 13	32	67	9,5	37,5	21,5
a	S 30 43 0 619 016	1"1/16 - 12 UN		5/8" 16	32	72	12,5	38	22
a	S 30 43 0 619 019	1"1/16 - 12 UN		3/4" 19	32	79	15	40	24
a	S 30 43 0 619 025	1"1/16 - 12 UN		1" 25	32	87	15	40	24
a	S 30 43 0 622 019	1"3/16 - 12 UN		3/4" 19	36	80,5	15	41,5	25
a	S 30 43 0 625 019	1"5/16 - 12 UN		3/4" 19	41	81	15	42	25
a	S 30 43 0 625 025	1"5/16 - 12 UN		1" 25	41	89	19,5	42	25
a	S 30 43 0 632 025	1"5/8 - 12 UN		1" 25	50	90,5	19,5	43,5	27
a	S 30 43 0 632 032	1"5/8 - 12 UN		1"1/4" 32	50	98,5	26	44	27,5
a	S 30 43 0 638 032	1"7/8 - 12 UN		1"1/4" 32	60	103,5	26	49	29,5
a	S 30 43 0 638 038	1"7/8 - 12 UN		1"1/2 38	60	107	32	49	29,5
a	S 30 43 0 650 050	2"1/2 - 12 UN		2" 50	75	131,5	42	59	35,5

a: dado pressato

a: crimped nut

a: aufgepresste Überwurfmutter