


Raccordi Femmina Sede JIC 74°
JIC Females 74° Cone
JIC 74° Dichtkegel


ISO 12151-5 (ISO 8434-2)

DKJ 90



CODICE Part n° Bestell. nr.	Filetto Thread Gewinde	Ø F ø F ø F	DN Tubo ND Hose DN Schlauch	CH	L	Ø C	H	M
a S 30 52 0 604 005	7/16" - 20 UNF		3/16" 05	14	47,5	3	26	25,5
a S 30 52 0 604 006	7/16" - 20 UNF		1/4" 06	14	57	4	26	29
a S 30 52 0 606 006	1/2" - 20 UNF		1/4" 06	17	57	4	27	29
a S 30 52 0 608 006	9/16" - 18 UNF		1/4" 06	19	57	4	28	29
a S 30 52 0 608 008	9/16" - 18 UNF		5/16" 08	19	57,5	5,5	30,5	29,5
a S 30 52 0 608 010	9/16" - 18 UNF		3/8" 10	19	63	7	35	33,5
a S 30 52 0 610 010	3/4" - 16 UNF		3/8" 10	24	63	7	37	33,5
a S 30 52 0 610 013	3/4" - 16 UNF		1/2" 13	24	71,5	9,5	42,5	42
a S 30 52 0 613 010	7/8" - 14 UNF		3/8" 10	27	63	7	38	33,5
a S 30 52 0 613 013	7/8" - 14 UNF		1/2" 13	27	71,5	9,5	43,5	42
a S 30 52 0 613 016	7/8" - 14 UNF		5/8" 16	27	87	12,5	54	53
a S 30 52 0 619 013	1"1/16 - 12 UN		1/2" 13	32	71,5	9,5	45	42
a S 30 52 0 619 016	1"1/16 - 12 UN		5/8" 16	32	87	12,5	54,5	53
a S 30 52 0 619 019	1"1/16 - 12 UN		3/4" 19	32	99	15	57,5	60
a S 30 52 0 622 019	1"3/16 - 12 UN		3/4" 19	36	99	15	58,5	60
a S 30 52 0 625 019	1"5/16 - 12 UN		3/4" 19	41	99	15	58,5	60
a S 30 52 0 625 025	1"5/16 - 12 UN		1" 25	41	126	19,5	70,5	79
a S 30 52 0 632 025	1"5/8 - 12 UN		1" 25	50	126	19,5	72,5	79
a S 30 52 0 632 032	1"5/8 - 12 UN		1"1/4 32	50	150,5	26	86	96
a S 30 52 0 638 032	1"7/8 - 12 UN		1"1/4 32	60	150,5	26	87	96
a S 30 52 0 638 038	1"7/8 - 12 UN		1"1/2 38	60	175,5	32	100,5	117,5
a S 30 52 0 650 050	2"1/2 - 12 UN		2" 50	75	216,5	42	135	144

DKJ 45



a S 30 82 0 604 006	7/16" - 20 UNF		1/4" 06	14	61,5	4	12,5	33,5
a S 30 82 0 606 006	1/2" - 20 UNF		1/4" 06	17	62	4	13,5	34
a S 30 82 0 608 006	9/16" - 18 UNF		1/4" 06	19	62,5	4	14	34,5
a S 30 82 0 608 008	9/16" - 18 UNF		5/16" 08	19	64	5,5	15	36
a S 30 82 0 608 010	9/16" - 18 UNF		3/8" 10	19	70,5	7	17,5	41
a S 30 82 0 610 010	3/4" - 16 UNF		3/8" 10	24	72	7	19	42,5
a S 30 82 0 610 013	3/4" - 16 UNF		1/2" 13	24	80,5	9,5	20,5	51
a S 30 82 0 613 010	7/8" - 14 UNF		3/8" 10	27	72,5	7	19,5	43
a S 30 82 0 613 013	7/8" - 14 UNF		1/2" 13	27	81,5	9,5	21,5	52
a S 30 82 0 613 016	7/8" - 14 UNF		5/8" 16	27	96,5	12,5	25,5	62,5
a S 30 82 0 619 013	1"1/16 - 12 UN		1/2" 13	32	82,5	9,5	22,5	53
a S 30 82 0 619 016	1"1/16 - 12 UN		5/8" 16	32	97	12,5	26	63
a S 30 82 0 619 019	1"1/16 - 12 UN		3/4" 19	32	108	15	28,5	69
a S 30 82 0 622 019	1"3/16 - 12 UN		3/4" 19	36	108,5	15	29	69,5
a S 30 82 0 625 019	1"5/16 - 12 UN		3/4" 19	41	108,5	15	29	69,5
a S 30 82 0 625 025	1"5/16 - 12 UN		1" 25	41	134,5	19,5	32,5	87,5
a S 30 82 0 632 025	1"5/8 - 12 UN		1" 25	50	135,5	19,5	34	88,5
a S 30 82 0 632 032	1"5/8 - 12 UN		1"1/4 32	50	161	26	41	106,5
a S 30 82 0 638 032	1"7/8 - 12 UN		1"1/4 32	60	162	26	42	107,5
a S 30 82 0 638 038	1"7/8 - 12 UN		1"1/2 38	60	184,5	32	46,5	126,5
a S 30 82 0 650 050	2"1/2 - 12 UN		2" 50	75	231	42	67	158,5

a: dado pressato

a: crimped nut

a: aufgepresste Überwurfmutter