


Raccordi maschi per tubi: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15
 Males for Hoses: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15
 Aussengewindenippel für Schläuche: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15

MAGN^{NPTF}

SAE J 516




CODICE Part n° Bestell. nr.	Filetto Thread Gewinde	Ø F ø F ø F	DN Tubo ND Hose DN Schlauch	CH	L	Ø C	D	E	
S 80 12 0 519 019	3/4" NPTF		3/4"	19	27	98	14	36	17
S 80 12 0 525 025	1" NPTF		1"	25	36	116	19	42	18
S 80 12 0 532 032	1" 1/4 NPTF		1" 1/4	32	46	124,5	25	44,5	20
S 80 12 0 538 038	1" 1/2 NPTF		1" 1/2	38	50	139,5	31	48	22,5
S 80 12 0 550 050	2" NPTF		2"	50	65	157	42	53	27

MAGR

BSP cilindrico Sede 60°
 BSP cylindrical 60° Cone
 BSP Zylindrisch 60° Konus

ISO 12151-6 (ISO 8434-6)




S 80 13 0 119 019	G 3/4"		3/4"	19	32	97,5	14	35,5	19,5
S 80 13 0 125 025	G 1"		1"	25	41	114,5	19	40,5	21,5
S 80 13 0 132 032	G 1" 1/4		1" 1/4	32	50	125,5	25	45,5	25,5
S 80 13 0 138 038	G 1" 1/2		1" 1/2	38	55	143,5	31	52	30
S 80 13 0 150 050	G 2"		2"	50	70	162	42	58	33

MAGJ

JIC 74° - UNF-UN

ISO 12151-5 (ISO 8434-2)



S 80 15 0 619 019	1" 1/16-12 UN		3/4"	19	27	102,5	14	40,5	18,6
S 80 15 0 625 025	1" 5/16-12 UN		1"	25	36	117	19	43	19,9
S 80 15 0 632 032	1" 5/8-12 UN		1" 1/4	32	46	127	25	47	22,7
S 80 15 0 638 038	1" 7/8-12 UN		1" 1/2	38	50	145,5	31	54	26,5
S 80 15 0 650 050	2" 1/2-12 UN		2"	50	65	169,5	42	65,5	31,6